

AS-1500 and AS-1500 G Offset Dish



Parameter	Unit	Numerical	Reflector Material:
Effective Reflector Size	mm	1515x1610	Glass Epoxy Metallised Composite (resistant to salt, air pollution)
Operating Frequency	GHz	10.7÷12.8	
Gain (for frequency in GHz)	10,7 dB	42,7	Colour: light grey (RAL 7047)
	11,3 dB	43,2	
	12,6 dB	44,1	Package Size (outside dimensions): 1÷2 units in Cardboard Box 1680x180x1595 mm
3dB Beamwidth (for frequency in GHz)	10,7 deg	1,3	
	11,3 deg	1,2	Compatible Accessories: ASZ-1500 Elevation over Azimuth Mount
	12,6 deg	1,1	
Focal Length	mm	1100	Wind Loading: Operational 80 km/h Survival 200km/h
Offset Angle	deg	20,1	
Feed Clamp Diameter	mm	40,0	Operating Temperature: Operational -40 ÷ 60 Survival -50 ÷ 80
Weight Reflector AS-1500/AS-1500 G	kg	13,0/16,0	
Weight AS-1500/AS-1500 G include Mount:	Az-El kg	18.5/21,5	
Power/Voltage electric anti-icing system (for AS-1500 G only)	W	320,0	
	V	AC 230	



LAMINAS Spółka z o.o.

38-430 MIEJSCE PIĄSTOWE ul. Dworska 50

Tel./fax: +48 134 362 067

Internet: www.laminas.com.pl

e-mail: laminas@laminas.com.pl